




Tagli ottimizzati

Profilo

Sagoma	Colore	% Sfrido	Intestatura A	Intestatura B	Lama 90	Lama 45
	RAL1013	2,92	50	50	10	10
SWA402						

Barre utilizzate

N° barre	Dim. barra	Ml. ottimizzati	Kg ottimizzati
68	6.500	442	455,26
68		442	455,26

Elenco tagli

Taglio mm.	N° tagli	Pos.	Pos. prof.	° Sx	° Dx
525	32	53	L	45	45
575	28	50	L	45	45
575	12	51	0	45	45
577,9	60	54	L	45	45
592	20	49	L	45	45
647,1	12	51	2	90	90
682	8	57	H	45	45
692	10	52	L	45	45
692	8	57	L	45	45
699,1	12	55	L	45	45
1.112,2	12	55	H	45	45
1.192	10	52	H	45	45
1.192	32	53	H	45	45
1.468,6	60	54	H	45	45
1.722,9	6	51	1	45	90
1.722,9	6	51	3	90	45
2.081,7	6	51	3	90	45
2.081,7	6	51	1	45	90
2.182	20	49	H	45	45
2.182	28	50	H	45	45

Rappresentazione grafica

49	49	54	53
2.180,4	2.180,4	1.467	523,4
N° barre 10			
Dim. Barra 6.400			
Resto Barra 2,4			
50	50	54	53
2.180,4	2.180,4	1.467	523,4
N° barre 14			
Dim. Barra 6.400			
Resto Barra 2,4			
51	51	54	55
2.080,9	2.080,9	1.467	697,5
N° barre 3			
Dim. Barra 6.400			
Resto Barra 28,9			
51	51	54	55
2.080,9	2.080,9	1.467	697,5
N° barre 3			
Dim. Barra 6.400			
Resto Barra 28,9			




Tagli ottimizzati

51	51	51	51	53				
1.722,1	1.722,1	1.722,1	647,1	523,4				
N° barre 2		Dim. Barra 6.400		Resto Barra 9,2				
51	51	51	51	53				
1.722,1	1.722,1	1.722,1	647,1	523,4				
N° barre 2		Dim. Barra 6.400		Resto Barra 9,2				
54	54	54	52	55				
1.467	1.467	1.467	1.190,4	697,5				
N° barre 6		Dim. Barra 6.400		Resto Barra 53,1				
54	54	54	52	52	53			
1.467	1.467	1.467	690,4	690,4	523,4			
N° barre 4		Dim. Barra 6.400		Resto Barra 25,2				
52	53	53	57	57	57	57		
1.190,4	1.190,4	1.190,4	690,4	690,4	680,4	680,4		
N° barre 1		Dim. Barra 6.400		Resto Barra 6				
53	53	55	55	55	49			
1.190,4	1.190,4	1.110,6	1.110,6	1.110,6	590,4			
N° barre 4		Dim. Barra 6.400		Resto Barra 27,4				
52	52	52	52	52	57	57		
1.190,4	1.190,4	1.190,4	690,4	690,4	680,4	680,4		
N° barre 1		Dim. Barra 6.400		Resto Barra 6				
53	53	53	57	57	57	57		
1.190,4	1.190,4	1.190,4	690,4	690,4	680,4	680,4		
N° barre 2		Dim. Barra 6.400		Resto Barra 6				
53	53	57	51	51	51	51	51	
1.190,4	1.190,4	690,4	647,1	647,1	647,1	647,1	647,1	
N° barre 1		Dim. Barra 6.400		Resto Barra 8,5				
53	57	51	51	51	49	49	49	49
1.190,4	690,4	647,1	647,1	647,1	590,4	590,4	590,4	590,4
N° barre 1		Dim. Barra 6.400		Resto Barra 116,7				
53	49	54	54	54	54	54	50	50
1.190,4	590,4	576,3	576,3	576,3	576,3	576,3	573,4	573,4
N° barre 12		Dim. Barra 6.400		Resto Barra 486,5				
53	50	50	50	50	51	51	51	51
1.190,4	573,4	573,4	573,4	573,4	573,4	573,4	573,4	573,4
N° barre 1		Dim. Barra 6.400		Resto Barra 518				
51	51	51	51	51	51	51	51	
573,4	573,4	573,4	573,4	573,4	573,4	573,4	573,4	
N° barre 1		Dim. Barra 6.400		Resto Barra 1.720				



Tagli ottimizzati

Profilo

Sagoma	Colore	% Sfrido	Intestatura A	Intestatura B	Lama 90	Lama 45
 SWA501	RAL1013	1,78	50	50	10	10




Barre utilizzate

N° barre	Dim. barra	Ml. ottimizzati	Kg ottimizzati
64	6.500	416	461,76
64		416	461,76

Elenco tagli

Taglio mm.	N° tagli	Pos.	Pos. prof.	° Sx	° Dx
616	10	49	L	45	45
700	10	49	L	45	45
781	6	55	2	64,903	70,097
781	6	55	4	70,097	64,903
790	8	57	H	45	45
800	10	52	L	45	45
800	6	55	3	70,097	70,097
800	8	57	L	45	45
1.000	5	56	0	30,988	32,466
1.104	5	56	1	32,466	26,546
1.132,8	5	56	2	26,546	30,988
1.200	16	53	L	45	45
1.216	7	50	L	45	45
1.216	6	51	0	45	45
1.300	7	50	L	45	45
1.300	10	52	H	45	45
1.300	16	53	H	45	45
1.300	6	55	1	45	64,903
1.300	6	55	5	64,903	45
1.606,7	6	51	2	90	90
1.800	6	51	1	90	90
1.800	6	51	3	90	90
1.900	30	54	H	45	45
2.000	6	55	0	45	45
2.200	30	54	L	45	45
2.300	10	49	H	90	45
2.300	10	49	H	45	90
2.300	7	50	H	90	45
2.300	7	50	H	45	90

Rappresentazione grafica


N° barre 1 Dim. Barra 6.400 Resto Barra 40

N° barre 5 Dim. Barra 6.400 Resto Barra 163,3

N° barre 5 Dim. Barra 6.400 Resto Barra 11,2



Tagli ottimizzati

50	50	56	49
2.300	2.300	1.104	616
N° barre 3	Dim. Barra 6.400	Resto Barra 40	
50	50	56	49
2.300	2.300	1.104	616
N° barre 1	Dim. Barra 6.400	Resto Barra 40	
50	50	56	49
2.300	2.300	1.000	700
N° barre 2	Dim. Barra 6.400	Resto Barra 60	
54	54	54	
2.200	2.200	1.900	
N° barre 15	Dim. Barra 6.400	Resto Barra 70	
55	55	50	56
2.000	2.000	1.300	1.000
N° barre 3	Dim. Barra 6.400	Resto Barra 60	
54	51	50	49
1.900	1.800	1.216	700
N° barre 1	Dim. Barra 6.400	Resto Barra 34	
54	54	51	49
1.900	1.900	1.800	700
N° barre 6	Dim. Barra 6.400	Resto Barra 60	
54	54	50	50
1.900	1.900	1.300	1.216
N° barre 1	Dim. Barra 6.400	Resto Barra 44	
51	51	50	52
1.800	1.606,7	1.300	800
N° barre 1	Dim. Barra 6.400	Resto Barra 43,3	
51	52	50	51
1.800	1.300	1.216	1.216
N° barre 1	Dim. Barra 6.400	Resto Barra 18	
51	50	50	50
1.800	1.300	1.216	1.216
N° barre 2	Dim. Barra 6.400	Resto Barra 18	
51	52	51	51
1.800	1.300	1.216	1.216
N° barre 1	Dim. Barra 6.400	Resto Barra 18	
52	52	53	53
1.300	1.300	1.300	1.200
N° barre 1	Dim. Barra 6.400	Resto Barra 50	




Tagli ottimizzati

Sagoma	Colore	ML reali	Kg reali	N°barre	Dim. barra	ML. ottimizzati	Kg ottimizzati	% Sfrido
 SWA402	RAL1013	422,298	434,967	68	6.500	442	455,26	2,919
 SWA407	RAL1013	18,566	17,136	3	6.500	19,5	17,998	3,251
 SWA411	RAL1013	18,566	20,33	3	6.500	19,5	21,352	3,251
 SWA501	RAL1013	402,184	446,424	64	6.500	416	461,76	1,783
 SWA503	bronzo	269,138	64,593	43	6.500	279,5	67,08	2,169
 SWA504	RAL1013	57,891	56,444	10	6.500	65	63,375	9,398
 SWA508	RAL1013	116,429	171,966	19	6.500	123,5	182,41	4,187
 SWA509	argento	269,138	61,363	43	6.500	279,5	63,726	2,169
 SWA510	RAL1013	25,168	10,118	4	6.500	26	10,452	1,662
 SWC403	POLI	412,006	0	66	6.500	429	0	2,423
		2.011,384	1.283,342			2.099,5		



Tagli ottimizzati

Profilo

Sagoma	Colore	% Sfrido	Intestatura A	Intestatura B	Lama 90	Lama 45
 SWL202	ROV-AM	4,22	50	50	10	10


Barre utilizzate

N° barre	Dim. barra	Ml. ottimizzati	Kg ottimizzati
157	3.000	471	0
157		471	0


Elenco tagli

Taglio mm.	N° tagli	Pos.	Pos. prof.	° Sx	° Dx
561	32	53	L	45	45
611	28	50	L	45	45
611	12	51	0	45	45
613,9	60	54	L	45	45
628	20	49	L	45	45
647,1	12	51	2	90	90
718	8	57	H	45	45
728	10	52	L	45	45
728	8	57	L	45	45
735,1	12	55	L	45	45
1.148,2	12	55	H	45	45
1.228	10	52	H	45	45
1.228	32	53	H	45	45
1.504,6	60	54	H	45	45
1.740,9	6	51	1	45	90
1.740,9	6	51	3	90	45
2.099,7	6	51	3	90	45
2.099,7	6	51	1	45	90
2.218	20	49	H	45	45
2.218	28	50	H	45	45

Rappresentazione grafica


N° barre 12 Dim. Barra 2.900 Resto Barra 14,9

N° barre 8 Dim. Barra 2.900 Resto Barra 34

N° barre 12 Dim. Barra 2.900 Resto Barra 34

N° barre 16 Dim. Barra 2.900 Resto Barra 48,1



Tagli ottimizzati

N° barre 6	Dim. Barra 2.900	Resto Barra 45,2
N° barre 6	Dim. Barra 2.900	Resto Barra 45,2
N° barre 6	Dim. Barra 2.900	Resto Barra 7,1
N° barre 6	Dim. Barra 2.900	Resto Barra 7,1
N° barre 10	Dim. Barra 2.900	Resto Barra 147,4
N° barre 6	Dim. Barra 2.900	Resto Barra 147,4
N° barre 10	Dim. Barra 2.900	Resto Barra 23,5
N° barre 8	Dim. Barra 2.900	Resto Barra 23,5
N° barre 8	Dim. Barra 2.900	Resto Barra 33,5
N° barre 18	Dim. Barra 2.900	Resto Barra 140,5
N° barre 13	Dim. Barra 2.900	Resto Barra 424
N° barre 6	Dim. Barra 2.900	Resto Barra 12,6
N° barre 2	Dim. Barra 2.900	Resto Barra 416



Tagli ottimizzati

51	51	51	51
611	611	611	611
N° barre 2		Dim. Barra 2.900	Resto Barra 416
50	50	51	51
611	611	611	611
N° barre 1		Dim. Barra 2.900	Resto Barra 416
51	51	53	53
611	611	561	561

Fabbisogno barre

Sagoma	Colore	ML reali	Kg reali	N°barre	Dim. barra	ML ottimizzati	Kg ottimizzati	% Sfrido
 SWL202	ROV-AM	435,402	0	157	3.000	471	0	4,225
 SWL207	ROV-AM	17,126	0	7	3.000	21	0	15,114
 SWL211	ROV-AM	17,126	0	7	3.000	21	0	15,114
 SWL301	ROV-AM	402,184	0	162	3.000	486	0	13,913
 SWL304	ROV-AM	57,891	0	25	3.000	75	0	19,479
 SWL308	ROV-AM	116,429	0	50	3.000	150	0	19,047
 SWL309	ROV-AM	283,548	0	101	3.000	303	0	3,086
 SWL340	ROV-AM	10,064	0	4	3.000	12	0	12,8
		1.339,771	0					